

Horizontal Blast Cleaning Machine Blastrac 2-20D



Shot Blasting



400 V, 50 Hz, 63 A, CEE



To pull



Working Speed :
0,5 - 33 m/min



560 Kg

UNDERGROUND	<input type="checkbox"/> Steel
	<input type="checkbox"/> Concrete
	<input type="checkbox"/> Stone
	<input type="checkbox"/> Asphalt
	<input type="checkbox"/> Others



1 400 mm

720 mm

1 950 mm

Blastrac 2-20D

- Working width : 550 mm
 Blasting capacity : up to 400 m² / h on concrete
 Working areas : large horizontal surfaces (factory halls, car parks, ramps, steel and metal bridges, runaways, airports...)
 •
 Wheel power : 22 kW
 Scope of supply : Shotblast machine 2-20D, User manual
 Optional starting kit : Dust collector 854 DCS / 20 m suction hose ø 150 mm / Magnetic broom 800 mm / Maintenance kit / Blastrac steel abrasive
 •
 • Please contact your Blastrac Expert for these options

Main assets :

- Closed circuit, dust free (if connected to an appropriate dust collector)
- Ideal machine for surface preparation professionals and specialists
- Efficient on all types of floors
- High performances but human size machine
- Very performing recycling system
- Abrasive consumption < 100 gr / m²
-
-


Industry working areas



Industrial flooring



Decontamination



Road Maintenance



Airport



Asphalt Blasting



BLASTRAC
An International Surface Preparation Technology