

Horizontal Blast Cleaning Machine Blastrac 2-20DT



Shot Blasting



400 V, 50 Hz, 63 A, CEE



To pull



Working Speed :
0,5 - 33 m/min



560 Kg

UNDERGROUND	<input type="checkbox"/> Steel
	<input type="checkbox"/> Concrete
	<input type="checkbox"/> Stone
	<input type="checkbox"/> Asphalt
	<input type="checkbox"/> Others



1 400 mm

720 mm

1 950 mm

Blastrac 2-20DT

Working width :	550 mm
Blasting capacity :	up to 400 m ² / h on concrete
Working areas :	large horizontal surfaces (factory halls, car parks, ramps, steel and metal bridges, runaways, airports...)
Wheel power :	2 x 11 kW
Scope of supply :	Shotblast machine 2-20DT, User manual
Optional starting kit :	Dust collector 854 DCS / 20 m suction hose ø 150 mm / Magnetic broom 800 mm / Maintenance kit / Blastrac steel abrasive
	Please contact your Blastrac Expert for these options


Main assets :

- Closed circuit, dust free (if connected to an appropriate dust collector)
- Ideal machine for surface preparation professionals and specialists
- Efficient on all types of floors
- High performances but human size machine
- Very performing recycling system
- 2 separate motors of 11 kW each
- Abrasive consumption < 100 gr / m²
-
-

Industry working areas



Industrial flooring



Road Maintenance



Decontamination



Airport



Asphalt Blasting



BLASTRAC
An International Surface Preparation Technology